



# TUCK TAPE® EVOFLASH

## PREMIUM FLASHING TAPE

Water leakage prevention is important to consider during construction of durable homes. Our Tuck Tape® EvoFlash™ Premium Flashing Tape provides optimal protection against air & water infiltration around door & window frames. This tape is made of a multi-layer UV protected polyethylene film coated with a permanent bond adhesive.

## FEATURES & BENEFITS

- Meets all AAMA 711-13 requirements, Type A, Level 3 (80°C/176°F)
- High shear adhesive provides excellent initial tack to surfaces
- Strong and durable holding power
- No primer required (AAMA 711-13 Type A) when applied on proper surfaces
- Film is flexible and conforms well around surfaces
- Seals around fasteners and nails
- Water and moisture resistant
- Prevents air infiltration
- Excellent resistance to UV



**BUILD ON TRUST**



1-800-474-8273 | tuckbuilding.com



## PRODUCT ATTRIBUTES

CHARACTERISTICS				
Product Code	505021002286	505521522286	505902282286	505303042286
Dimensions (mm x m)	100mm x 22.86m	152mm x 22.86m	228mm x 22.86m	304mm x 22.86m
Rolls/Case	12	8	4	4
Product UPC	0-67735-50502-6	0-67735-50552-1	0-67735-50590-3	0-67735-50530-9
Backing	Multi-layered UV protected polyethylene film	Multi-layered UV protected polyethylene film	Multi-layered UV protected polyethylene film	Multi-layered UV protected polyethylene film
Adhesive	UV cured acrylic	UV cured acrylic	UV cured acrylic	UV cured acrylic
Color	Red film with black print	Red film with black print	Red film with black print	Red film with black print
Thickness	9.2 mil (0.23mm)	9.2 mil (0.23mm)	9.2 mil (0.23mm)	9.2 mil (0.23mm)
Tensile	14 lb/in (62 N/25mm)	14 lb/in (62 N/25mm)	14 lb/in (62 N/25mm)	14 lb/in (62 N/25mm)
Adhesion to Steel	100 oz/in (109.5 N/100mm)	100 oz/in (109.5 N/100mm)	100 oz/in (109.5 N/100mm)	100 oz/in (109.5 N/100mm)
Elongation	650%	650%	650%	650%
Case UPC	1-00-67735-50502-3	1-00-67735-50552-8	1-00-67735-50590-0	1-00-67735-50530-6



## PRODUCT APPLICATIONS

- Waterproof flashing membrane used to seal around windows and doors frames
- Recommend on aluminum, wood, wood clad, fiberglass, vinyl windows and doors
- Recommend on most house wraps, OSB, exterior gypsum and fibre board
- All above surfaces have to be dry and clean in order to assure proper contact

## MARKETS

- Building and Construction

For optimal performance, complete the building envelope with our full line of Tuck® Building products:

**NovaSeal**  
by Tuck

Roof Underlayments

**Tuck NovaWrap**  
Premium Building Wrap  
Enveloppe de bâtiment haut de gamme

Breathable Building Wrap  
(Air Barrier)

**Tuck Tape EvoFlash**  
Premium Flashing Tape  
Ruban pour solin haut de gamme

**Tuck Tape NovaFlash**  
Flashing Tape  
Ruban pour solin

Window and Door Flashing Tapes

**Tuck Tape**

Sheathing Tapes



Scan for more info or visit [www.tuckbuilding.com](http://www.tuckbuilding.com)

