



TUCK TAPE® NOVAFLASH

PROTECTION OF DOOR & WINDOW OPENINGS FROM WATER INTRUSION

Tuck Tape® NovaFlash™ is a self-adhered flashing tape comprised of a woven polypropylene (PP) backing with an aggressive hybrid butyl adhesive and an easy-to-remove polyethylene (PE) release liner. It meets AAMA 711 Standards, with features such as nail sealability and high performing adhesion without primer needed.



FEATURES & BENEFITS

- Meets all AAMA 711-13 requirements, Type A, Level 3 (80°C/176°F)
- High shear adhesive provides excellent initial tack to surfaces
- High strength puncture resistant
- No primer required (AAMA 711-13 Type A)
- Split release liner allows for easier and faster installation
- Seals around fasteners and nails (ASTM D1970)
- Water, moisture and mold resistant
- Prevents air infiltration
- Excellent resistance to UV

BUILD ON TRUST



1-800-474-8273 | tuckbuilding.com



PRODUCT ATTRIBUTES

CHARACTERISTICS				
Product Code	99446	99447	99448	99441
Dimensions mm x m (in x yd)	101.6 x 22.86 (4 x 25)	152.4 x 22.86 (6 x 25)	228.6 x 22.86 (9 x 25)	304.8 x 22.86 (12 x 25)
Rolls/Case	8	8	4	4
Product UPC	0 87143 00328 0	0 87143 00330 3	0 87143 00332 7	0 87143 00612 0
Release Liner	Split liner made of white polyethylene (PE)	Split liner made of white polyethylene (PE)	Split liner made of white polyethylene (PE)	Split liner made of white polyethylene (PE)
Adhesive	Butyl	Butyl	Butyl	Butyl
Backing	Woven polypropylene (PP)	Woven polypropylene (PP)	Woven polypropylene (PP)	Woven polypropylene (PP)
Color	Beige with red print	Beige with red print	Beige with red print	Beige with red print
Thickness	13 mil	13 mil	13 mil	13 mil
Tensile	85 lb/inch	85 lb/inch	85 lb/inch	85 lb/inch
Adhesion	55 oz/inch	55 oz/inch	55 oz/inch	55 oz/inch
Elongation	21%	21%	21%	21%
Case UPC	2 00 87143 00328 4	2 00 87143 00330 7	2 00 87143 00332 1	2 00 87143 00612 4



PRODUCT APPLICATIONS

- Waterproof flashing membrane used to seal window and door openings
- Recommend on aluminum, wood, wood clad, fiberglass, vinyl windows and doors
- Recommend on most house wraps, OSB, exterior gypsum and fibre board
- All above surfaces have to be dry and clean in order to assure proper contact

MARKETS

- Building and Construction

For optimal performance, complete the building envelope with our full line of Tuck® Building products:

NovaSeal
by Tuck

Roof Underlayments

Tuck NovaWrap
Premium Building Wrap
Enveloppe de bâtiment haut de gamme

Breathable Building Wrap
(Air Barrier)

Tuck Tape EvoFlash
Premium Flashing Tape
Ruban pour solin haut de gamme

Tuck Tape NovaFlash
Flashing Tape
Ruban pour solin

Window and Door Flashing Tapes

Tuck Tape

Sheathing Tapes



Scan for more info or visit www.tuckbuilding.com

