



A REGISTERED TRADEMARK OF INTERTAPE POLYMER INC.

Tuck Tape NovaFlash®

SELF-ADHERED WATER PROTECTION BUTYL WINDOW & DOOR FLASHING



DESCRIPTION

Tuck Tape® NovaFlash® is a self-adhered flashing tape comprised of a woven polypropylene (PP) backing with an aggressive hybrid butyl adhesive and an easy-to-remove polyethylene (PE) release liner. It meets AAMA 711 Standards, with features such as nail sealability and high performing adhesion without primer needed.

MAIN FEATURES

- Meets all AAMA 711-13 requirements, Type A, Level 3 (80°C/176°F)
- High shear adhesive provides excellent initial tack to surfaces
- High strength puncture resistant
- No primer required (AAMA 711-13 Type A)
- Split release liner allows for easier and faster installation
- Seals around fasteners and nails (ASTM D1970)
- Water, moisture and mold resistant
- Prevents air infiltration
- Excellent resistance to UV

APPLICATIONS

- Waterproof flashing membrane used to seal window and door openings
- Recommend on aluminum, wood, wood clad, fiberglass, vinyl windows and doors
- Recommend on most house wraps, OSB, exterior gypsum and fibre board
- All above surfaces have to be dry and clean in order to assure proper contact

TECHNICAL DATA

Backing	Woven coated, polypropylene (PP) facer
Release Liner.....	Split white polyethylene (PE) film
Adhesive.....	Butyl-Rubber
Thickness.....	13 mil ± 10%
ASTM D1777	
Nail Sealability.....	Pass (Initial Observation)
ASTM D1970M section 7.9	Pass (After thermal cycling)
Peel Adhesion (90°).....	55 oz/in (OSB)
AAMA 711 section 5.3-5.6	66 oz/in (Aluminum)
ASTM D3330	67 oz/in (Vinyl)
	64 oz/in (Plywood) - 84 oz/in (Elevated Temp.)
	91 oz/in (Thermal Cycling) - 90 oz/in (Accelerated Aging)
Cold Temperature Pliability	-18°C (0°F)
ASTM D1970M section 7.6	
Application Temperature Range	-5°C (23°F) à 50°C (122°F)
Service Temperature Range.....	-40°C (-40°F) à 121°C (250°F)
Tensile Strength.....	85 oz/in
ASTM D5035	
Elongation at Break.....	21%ASTM D5035
Peeling Resistance	No - Peeling
AAMA 711 section 7.9	No - Buckling
No- Rippling - 0 in - Max. Edge Curl - 0 in - Max. Corner Curl	
Color.....	Beige with red print

PERMANENT BOND

HIGH SHEAR ADHESIVE

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warranties or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

Meets ASTM E2112 for Flashing
Exterior Windows & Doors

Meets AAMA 711
• Adhesion Rating Type A (no primer)
• Thermal Exposure (Class 3, 80°C)

Intertape Polymer Inc. 9999 Cavendish Blvd, Suite 200, Montréal, QC H4M 2X5 **Phone: 1.800.334.1567**
Cantech Industries Inc. 100 Paramount Drive, Suite 300, Sarasota, FL 34232 **Phone: 1.800.654.3947**

cantech.com

030124